




● **APPLICATIONS**

- Both side printing
- **Digital printing:** solvent / eco-solvent UV and Latex inks
- **Indoor communication:** signage / banners / POS

● **PRODUCT PACKAGING**

- **Super Wide format:** 2.78m / 3.10m  
Rolls of: 60 ml - printable side outside  
0.90m / 1.00m / 1.10m  
Packaging: 4 rolls of 60 ml/pallet - printable side outside
- **Wide Format:** 1.02m / 1.37m / 3.10m  
Rolls of: 25 ml - printable side outside

● **PRODUCT CHARACTERISTICS**

<b>Weight</b>	<b>680 g/m<sup>2</sup></b>		
<b>Coating</b>	PVC coating System LOWICK	<b>Base cloth</b>	High tenacity polyester 550 Dtex
<b>Colour</b>	White 7326	<b>Finish</b>	Satin inkjet lacquer Both side
<b>Thickness</b>	0.49 mm	<b>Translucency XP T 54 199</b>	0 %
<b>Tensile strength NF EN ISO 1421</b>	180 / 150 daN	<b>Tear strength DIN 53363</b>	20 / 20 daN
<b>Temperature Stability</b>	-30°C to +70°C -22°F to + 158°F	<b>Adhesion NF EN ISO 2411</b>	6 daN/5cm
<b>F / R</b> 	<b>M2 / B1 NFPA 701</b>		



● **DICKSON COATINGS**

Company with management system certified by DNV-GL  
= ISO 9001 =  
= ISO 14001 =

[www.dickson-coatings.com](http://www.dickson-coatings.com)